ACCESSORIES

Timer

Specification

Model	KLT-R
Supply Voltge	24..240V AC/DC-50Hz/60Hz for "CE"marked Timer
Absorption Current	4mA Max
Operating Temperature	-10℃~+50℃
Class Protection	IP65-EN 60529
Switch Holding Voltage	400V Max
Switch Capacity	1A
Inrush Current	10A for 10 ms
Duty Cycle	100%ED
Switch Life	3x108
Time ON	from 0.5 to 10s.
Time OFF	from 0.5 to 45min
Indicators	Green LED for "ON", Red LED for "OFF"
Manual Override	Test
Connection	DIN43650A

Model	KLT-S
Supply Voltge	24..240V AC/DC-50Hz/60Hz for "CE"marked Timer
Absorption Current	4mA Max
Operating Temperature	-10℃~+50℃
Class Protection	IP65-EN 60529
Switch Holding Voltage	400V Max
Switch Capacity	1A
Inrush Current	10A for 10 ms
Duty Cycle	100%ED
Switch Life	3x108
Time ON	from 0.5 to 10s.
Time OFF	from 0.5 to 45min
Indicators	Green LED for "ON", Red LED for "OFF"
Manual Override	Test
Connection	DIN43650A

Model	KLT-E
Supply Voltge	24..240V AC/DC-50Hz/60Hz for "CE"marked Timer
Absorption Current	4mA Max
Operating Temperature	-10℃~+50℃
Class Protection	IP65-EN 60529
Switch Holding Voltage	400V Max
Switch Capacity	1A
Inrush Current	10A for 10 ms
Duty Cycle	100%ED
Switch Life	3x108
Time ON	from 0.5 to 9.5s step 0.5s. / from 10 to 99min step 1s.
Time OFF	from 0.5 to 9.5s step 0.5min. / from 10 to 99min step 1min.
Indicators	Green LED for "ON", Red LED for "OFF"
Manual Override	Test
Connection	DIN43650A